

Order form

Orderer

Valid from 04.01.2016 Order no.

CL31 Lidar Ceilometer

aisala Ceilometer	CL31 C 1 1 1 PR
Operating voltage	100-115 VAC 1
	230 VAC 2
Reserved	c
CSP Model	No 1
	CL31BL (with aerosol settings) A
	CL31-cETL (for Canadian markets) B
	CL31-AQ Air quality package with PC and accessories D
Data line interface	RS232 A
	RS485 B
	Modem (DXL421 modem module) C
	LAN (ETH-CL31) D
Reserved	1
Software	Standard A A A
	Standard + Sky Condition B
Cable Termination	No 1
Box	Box with additional transient protection (Termbox-1200)
	Box without additional transient protection (CLTERMBOX) 3
Bird deterrent device	No A
	Bird deterrent device (CL31BIRDKIT)
Optical Termination	No 1
Hood	Needed for indoor service (CLTERMHOOD) 2
Service Cable	No A
	RS cable for local maintenance access (QMZ101) B B
	USB cable for local maintenance access (CL31USBCABLE) C
Application Software	No 1
	CL-VIEW Cloud Reporting Software for Ceilometers 2 2
	BL-VIEW Boundary Layer Software for Ceilometers 3 3
	BL-VIEW and CL-VIEW for Air Quality package
Shock Absorber	No A
	CT35022, recommended for marine and off-shore installations B
Internal Humidity	No 1
Transmitter	Humidity transmitter (CLHUMITTER)
Radio Modem Kit	No A
	Attachment mechanics for radio modem antenna (CLRADIOKIT)
Reserved	1
Manual language	No manual A
	English B
	French
	Chinese
	Spanish E
	Russian F
	TOTAL
	QTY
	TOTAL VALUE

Selections in bold are included in the prices of the basic versions.

Selections in italic are available at an extra price.

Example of order code with typical settings:

CL31	2	ဂ	1	Α	1	Α	2	Α	1	В	1	Α	1	Α	1	В
------	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

Fnd	customer:
LIIU	Custoniei.

Recommended accessories:

Accessory
Drilling template cETL testing procedure for 1 to 15 units <u>Code</u> CT45182 CETLTESTING-CL