VAISALA

Take the Lab to the Field Vaisala Barometric Pressure Transfer Standard PTB330TS



Operational PTB330TS unit includes a PTB330 digital barometer, hand-held MI70 indicator, optional HMP155 humidity and temperature probe, optional MI70 Link PC software, a user's guide and a weatherproof transfer case equipped with a shoulder strap.



PTB330TS transport case

Barometric Pressure Transfer Standard PTB330TS makes field inspection accurate and easy. It combines a PTB330 digital barometer with a hand-held MI70 indicator within a portable unit functioning as a transfer standard. The optional HMP155 probe is available for accurate humidity and temperature measurement.

The PTB330TS is suitable for various reference measurements in industrial and meteorological areas.

The PTB330TS comes in a durable and weatherproof transport case that can be easily carried and shipped. The components are placed in a proofing foam interior, with accessories and user's guide placed in the lid organizer. The case includes a separate inner tabletop case in which the barometer is mounted. Shoulder strap is included for convenience. Battery duration is up to 11 hours of continuous use and up to 30 days in data logging use.

Features / Benefits

- Portable, battery operated transfer standard with data logging capability
- Barometric pressure with Vaisala BAROCAP[®] Digital Barometer PTB330
 - Excellent long term stability
 - Accurate measurements
 - Added reliability through redundancy

- Optional humidity and temperature measurements with HMP155
 - Vaisala HUMICAP®180R sensor
 superior long-term stability
 - New, fast temperature probe
 - Chemical purge
- Multilingual user interface, nine languages
- Data can be logged, and transferred to a PC via MI70 Link software
- SO/IEC 17025 Accredited calibration services available
- For professional meteorology, aviation, laboratories and demanding industrial applications







The HMP155 probe



The MI70 hand-held indicator displaying the prevailing pressure in hPa

PTB330 Digital Barometer

Vaisala BAROCAP® Digital Barometer PTB330 is a new generation barometer designed for a wide range of high-end atmospheric pressure measurement. The pressure measurement of the PTB330 is based on the Vaisala in-house, silicon capacitive, absolute pressure sensor – the Vaisala BAROCAP® Sensor. It provides high measurement accuracy and excellent long-term stability.

High Accuracy

The PTB330 series features extremely high accuracy. Class A barometers for the most demanding applications are fine-adjusted and calibrated against a high-precision pressure calibrator. All the PTB330 barometers come with a NIST traceable, factory calibration certificate, also optional ISO/IEC 17025 accreditation calibration services are available.

Reliability through Redundancy

According to customers' choice, the PTB330 can incorporate one, two or three BAROCAP® sensors. When two or three sensors are used, the barometer continuously compares the readings of the pressure sensors against one another and provides information on whether these are within the set internal difference criteria. This unique feature provides redundancy in pressure measurement. Thus, users get a stable and reliable pressure reading at all times as well as a pre-indication of when to service or re-calibrate the barometer.

Optional HMP155 Humidity and Temperature Probe

The new Vaisala HUMICAP[®] Humidity and Temperature Probe HMP155 provides reliable humidity and temperature measurement.

Long-Term Stability

The HMP155 has a new generation Vaisala HUMICAP®180R sensor that has excellent stability and withstands harsh environments well. The probe structure is solid and the sensor is protected with a sintered teflon filter, which gives maximum protection against liquid water, dust, and dirt.

Fast Temperature Measurement

What's more, with its fast response time, the additional temperature

probe for the HMP155 is ideal for measurement in environments with rapidly changing temperatures.

MI70 Hand-Held Indicator for Spot-Checking Applications

The Vaisala Measurement Indicator MI70 is a user-friendly indicator for demanding spot-checking measurements. It is ideal for field checking and calibration of Vaisala's fixed instruments.

Easy-to-Use User Interface and Three-Variable Display

The MI70 features a multilingual, menu-based user interface, and a clear graphical LCD display. Overall three measurement parameters can be displayed and logged into the meter's memory at the same time. One or two probes or transmitters can be connected simultaneously.

MI70 Link

The optional MI70 Link Windows[®] software and the USB connection cable form a practical tool for transferring logged data and real time measurement data from the MI70 to a PC.



For more information, visit www.vaisala.com or contact us at sales@vaisala.com Ref. B210785EN-B ©Vaisala 2011 This material is subject to copyright protection, with all copyrights retained by Vaisala and its individual partners. All rights reserved. Any logos and/or product names are trademarks of Vaisala or its individual partners. The reproduction, transfer, distribution or storage of information contained in this brochure in any form without the prior written consent of Vaisala is strictly prohibited. All specifications – technical included – are subject to chance without notice.